

RAD MOUNT (Rafter And Decking)

The integrated L-foot & Flash design provide flexibility to mount to either the Rafter or Decking on composition/asphalt shingle Roofs. The innovative Pad design helps mitigate shingle height variation. Each mount comes with 6 attachment screws, 6 EPDM washers, 1-tbolt, and 1 attachment nut – All at not extra charge! Installers love the ease and faster install times with this new Radical design!

PRODUCT LINE

Item

CK-FTS-167RT2

Product Name

Rad Mount Chiko Al Roof Hook #167

TECHNICAL DATA

Main Material	: AL 6005-T5
Uplift P	: N*Fv (N=3)
Wind Velocity	: Up to 60 M/S (134 MPH)
Snow Load	: 1.4 KN/m ²
Hook Spacing	: Up to 2000mm
Installation Site	: Asphalt Shingles

ORDERING SPECIFICS

Standard Packaging	: 25PCS/CTN
Dimensions	: 45x27x30/CM
Weight	: 21KG

ADVANTAGES

- Optional Holes provided for Rafter & Decking
- Flexible moving on orientations Vertical & Horizontal
- Water-proof with thermoplastic butyl adhesive
- Faster Install Time

WARRANTY



INTERTEK LISTED



COMPONENT LIST

Material

Rad Mount #167 Hook	01
SUS304 T2 Bolt M8*30	01
SUS304 Flange nut M8	01
Wooden Screw M6.3*65	06
Self-Adjusting Foam Pad	01
EPDM Washer	06
Butyl rubber	01

QTY

